

DOSKO

STUMP GRINDER

the mini and mid-size

Both fit in a SUV or Minivan

NEW!

200-6H (MINI)

POWERED BY HONDA

LEONARDI® TEETH



NEW!

270-9H (MID-SIZE)

POWERED BY HONDA

GREENTEETH®



MINI & MID-SIZE
WALK-BEHINDS

www.dosko.com

STANDARD FEATURES

FOLDABLE

Our Mini and Mid-Size stump grinders' handles fold to reduce unit transport sizes to:

MINI

- 36" L x 23" W x 23" H

MID-SIZE

- 52" L x 32.5" W x 26" H

3-IN-1 TOOTH SYSTEM

Our 3-in-1 tooth system allows you to rotate each of your stump grinder's teeth in three, 120° increments for a fresh cutting edge.

LIGHTWEIGHT

At under 200 pounds, both the Mini and Mid-Size are easy to operate, but provide the power you need with 200 and 270 cc's respectively.

SPECIFICATIONS

DOSKO
STUMP GRINDER
the mini and mid-size



	200-6H (MINI)	270-9H (MID-SIZE)
ENGINE OPTIONS		
Make	Honda	Honda
Model	GX200UTGX2	GX270UT2QAG2
CC Rating	200 cc	270 cc
GENERAL		
Weight	134 lbs. (61 kg)	199 lbs. (90 kg)
Length/Folded Length	56"/36" (142 cm/92 cm)	62"/52" (156 cm/132 cm)
Width	23" (58 cm)	32.5" (83 cm)
Height/Folded Height	45"/23" (114 cm/59 cm)	42"/26" (107 cm/66 cm)
RPM Operating	3600 RPM	3600 RPM
Type of Fuel	Gasoline	Gasoline
Starting	Recoil	Recoil
Oil Sensor	Honda (yes)	Honda (yes)
CUTTER WHEEL		
Diameter	10.5" (27 cm)	11" (28 cm)
Thickness	1/2" (1.27 cm)	3/8" (.95 cm)
Bearings (Dia.) (2)	1" (2.5 cm)	1" (2.5 cm)
3-In-1 Tooth System (Carbide Tips)	Leonardi® (3 Teeth)	Greenteeth® (6 Teeth)
	1" Dia. (2.5 cm)	1/2" Dia. (1.27 cm)
	.2" Thick (.508 cm)	1/4" Thick (.635 cm)
	3-Position Rotating Teeth	3-Position Rotating Teeth
Disc RPM	4700 RPM	3600 RPM
	Direct Belt Drive	Direct Belt Drive
Drive	AX Gates Belt (1)	BX Gates Belt (1)
	1600 Series Noram Clutch	3 Groove Power Band with Idler Bearing Belt Tensioners
CUTTING CAPACITY		
Above Grade	10" (25 cm)	12" (30 cm)
Below Grade	9" (23 cm)	11" (28 cm)
Stump Diameter	No Limit	No Limit
GROUND TRAVEL		
Speed	Push-Pull Type	Push-Pull Type
Drive	Wheel Hub	Wheel Hub
Tires (2)	12.5", 410-350 X 6"	15" x 600 X 6"
Brake	Wheel Hub with Adjustable Brake Band	Wheel Hub with Adjustable Brake Band
OPTIONAL TOW PACKAGES		
Tow Package Model	N/A	N/A

DOSKO
www.dosko.com

ITEM# DOSSTUMPLIT.DOS

My Authorized Dosko Sales & Service Dealer:

DOSKO/GREAT NORTHERN EQUIPMENT

20195 South Diamond Lake Road, Suite 100 • Rogers, MN 55374 / Toll-Free: 800-822-0295 / Fax: 763-428-4821 / www.dosko.com

DOSKO

STUMP GRINDER



TWO NEW MODELS
NOW AVAILABLE!



www.dosko.com

EIGHT MODELS



DOSKO STUMP GRINDER

FULL SIZE
WALK-BEHINDS

FULL SIZE
WALK-BEHINDS

PORTABILITY

Models 337-13H, 357-13HE, 620-20HE and 620-25KE are towable and can easily be hooked up to a vehicle for towing in a matter of minutes. Rental companies have cut costs considerably not having a need for trailers, license fees, etc. While models 691SP-20HE and 691SP-25KE aren't towable, they can easily be self-propelled up a ramp and loaded for transporting in a pickup truck or small utility trailer.

HD BANDED BELT & IDLER BEARINGS

The heavy duty belt(s) and idler bearings have proven to be long-lasting, key components in our stump grinder's overall operating performance. Less belt tension is needed with the idler bearings, which reduces excess side loads to the engine and cutter wheel bearings, increases engine and bearing life, ensures smoother running belts with less vibration and slipping, and reduces costly downtime and maintenance.

SIDE DISCHARGE FRAME

Dosko's unique frame design discharges the cuttings out and away from the machine automatically while grinding. This means much less clean-up than would be required with a channel frame stump grinder.



BAIL/OPERATOR CONTROL HANDLE

A double bow handlebar allows the operator free, unrestricted movement while grinding. In addition, the control bar provides the operator easy access to controls at all times and is equipped with an operator-presence shut-down switch for additional safety.

ADJUSTABLE HANDLEBAR

With five handlebar position adjustments available, the operator is sure to find a comfortable working position to maintain complete control of the machine while grinding.

ACCESSIBILITY

Dosko stump grinders are designed to be 32" and less in width. This allows them to be transported through narrow paths, walkways and gates making them very portable for backyard access.

DOSKO STUMP GRINDER



	337-13H	357-13HE	620-20HE	620-25KE	691SP-20HE	691SP-25KE
ENGINE OPTIONS						
Make	Honda	Honda	Honda	Kohler	Honda	Kohler
Model	GX390UT1QAA2	GX390UT1QAE2	GX620R1TXF2	CH730-0002	GX620R1TXF2	CH730-0002
CC Rating	390 cc	390 cc	620 cc	721 cc	620 cc	721 cc
GENERAL						
Weight	300 lbs. (136 kg)	350 lbs. (159 kg)	400 lbs. (181 kg)		500 lbs. (227 kg)	
Length	58" (147 cm)	58" (147 cm)	58" (147 cm)		85" (218 cm)	
Width	32" (81 cm)	32" (81 cm)	32" (81 cm)		30" (76 cm)	
Height	51" (130 cm)	51" (130 cm)	51" (130 cm)		56" (142 cm)	
RPM Operating	3600 RPM	3600 RPM	3600 RPM		3600 RPM	
Type of Fuel	Gasoline	Gasoline	Gasoline		Gasoline	
Starting	Recoil	Recoil & Electric	Electric		Electric	
Oil Sensor	Honda (yes)	Honda (yes)	Kohler (yes), Honda (yes)		Kohler (yes), Honda (yes)	
CUTTER WHEEL						
Diameter	14" (36 cm)	14" (36 cm)	14" (36 cm)		14" (36 cm)	
Thickness	3/8" (.95 cm)	3/8" (.95 cm)	3/8" (.95 cm)		3/8" (.95 cm)	
Bearings (Dia.) (2)	1 3/16" (3 cm)	1 3/16" (3 cm)	1 3/16" (3 cm)		1 3/16" (3 cm)	
Teeth Pockets	Reversible	Reversible	Reversible		Reversible	
	Greenteeth®	Greenteeth®	Greenteeth®		Greenteeth®	
Teeth (8) (Carbide Tips)	1/2" Dia. (1.27 cm) 1/4" Thick (.635 cm)	1/2" Dia. (1.27 cm) 1/4" Thick (.635 cm)	3/4" Dia. (1.9 cm) 1/4" Thick (.635 cm)		3/4" Dia. (1.9 cm) 1/4" Thick (.635 cm)	
Disc RPM	2200 RPM	2200 RPM	2500 RPM		3000 RPM	
Drive	Direct Belt Drive	Direct Belt Drive	Direct Belt Drive		Electromagnetic Clutch	
	1 Banded Gates Belt	1 Banded Gates Belt	1 Banded Gates Belt		2 Gates Belts	
	3 Groove Power Band with Idler Bearing Belt Tensioners	3 Groove Power Band with Idler Bearing Belt Tensioners	4 Groove Power Band with Idler Bearing Belt Tensioners		2V-Belts with Idler Bearing Belt Tensioners	
CUTTING CAPACITY						
Above Grade	20" (51 cm)	20" (51 cm)	20" (51 cm)		24" (61 cm)	
Below Grade	16" (41 cm)	16" (41 cm)	16" (41 cm)		18" (46 cm)	
Stump Diameter	No Limit	No Limit	No Limit		No Limit	
GROUND TRAVEL						
Speed	Push-Pull Type; Towable	Push-Pull Type; Towable	Push-Pull Type; Towable		0-3 MPH (0-4 KPH); Not Towable	
Drive	Wheel Hub	Wheel Hub	Wheel Hub		Hydrostatic Drive	
Tires (2)	4.80/4.00-8" (20 cm)	4.80/4.00-8" (20 cm)	4.80/4.00-8" (20 cm)		16x6.50-8" (20 cm)	
Brake	Wheel Hub with Adjustable Brake Band	Wheel Hub with Adjustable Brake Band	Wheel Hub with Adjustable Brake Band		Disc Brake with Adjustable Brake Pads	
OPTIONAL TOW PACKAGES						
Tow Package Model	337-357TP	337-357TP	620-TP		N/A	

SPECIFICATIONS

STANDARD
FEATURES

GREENTEETH®

Our stump grinders utilize Greenteeth®, the industry leading, carbide-tipped stump grinding teeth. Greenteeth® take shock very well and excel in rocky soil. **(STANDARD ON 337/357 & 620/691SP)**

BUILT-IN OWNER'S MANUAL

A steel tube built into the stump grinder houses the owner's manual and safe operation guide making it easily available for quick reference.

TOWING SAFETY

An ability to attach two towing safety chains mean extra assurance that your stump grinder stays with you in transport. Recommended maximum towing speed is 45 MPH. **(OPTIONAL)**

“THE FASTEST
EASIEST-TO-USE PORTABLE
STUMP GRINDER”
ON THE MARKET TODAY

www.dosko.com

DOSKO
STUMP GRINDER